

2024-05-03

 SWEDSTYLE



AERO C-3

Electric adjustable Sit & Stand frame for an ergonomic and flexible work environment around the meeting table.

- Many different size options
- Ergonomic
- Design it yourself

AERO frame for meeting tables in a robust design, with electric height-adjustment, allows the creation of an ergonomic and flexible work environment at tables where many people meet. Because AERO can be assembled together with any table top and is available in a range of sizes, creating a table to suit the needs of the business or activity is easy. Rectangular legs in an elegant design.

Art. no	Feet	Colour	Height
505120 + 502370	_reL_2588	Chrome	1050
505130 + 502370	_reL_2596	Chrome	1050
505128 + 502378	_reL_2588	Silver	1050
505138 + 502378	_reL_2596	Silver	1050
505125 + 502375	_reL_2588	Black	1050
505135 + 502375	_reL_2596	Black	1050
505126 + 502376	_reL_2588	White	1050
505136 + 502376	_reL_2596	White	1050
505120	_reL_2588	Chrome	700
505130	_reL_2596	Chrome	700
505128	_reL_2588	Silver	700
505138	_reL_2596	Silver	700
505125	_reL_2588	Black	700
505135	_reL_2596	Black	700
505126	_reL_2588	White	700
505136	_reL_2596	White	700
505120 + 502360	_reL_2588	Chrome	900
505130 + 502360	_reL_2596	Chrome	900
505128 + 502368	_reL_2588	Silver	900
505138 + 502368	_reL_2596	Silver	900
505125 + 502365	_reL_2588	Black	900
505135 + 502365	_reL_2596	Black	900
505126 + 502366	_reL_2588	White	900
505136 + 502366	_reL_2596	White	900
505930	_reL_2588	Chrome	700-1000
505940	_reL_2596	Chrome	700-1000
505938	_reL_2588	Silver	700-1000
505948	_reL_2596	Silver	700-1000
505935	_reL_2588	Black	700-1000
505945	_reL_2596	Black	700-1000
505936	_reL_2588	White	700-1000
505946	_reL_2596	White	700-1000

Technical specifications

AERO C-3



Specification	Value
Adjustable height	Yes
Powered by	Electricity
Frame width	2240 - 3470 mm
Stroke	400 mm (675 - 1075 mm $\pm$ 5 mm)
Lift capacity	Max 100 kg
Speed	30 mm/sek
Standby power	0,3 W
Noise level	< 42 dBa
Dimensions tabletops	2260 - 4170 mm x 800 - 1500 mm
Certifications	SS EN 15372 CE Compliant
Duty cycle	10%, 1 min/9 min pause. Max 2 min/18 min
Installation height down position	675 mm
Paintwork	Powder coating
Area of use	Indoor environment Ambient temperature: +5° to +30° C Humidity: 5 - 85% non condensed
Control unit performance	Low inbuilt height dimensions Switching technology without any magnetic fields Inbuilt overload protection Inbuilt temperature protection
Lifetime	Min 10 000 cycles