

2024-05-06

 SWEDSTYLE



AERO C-4

Electric adjustable Sit & Stand frame for an ergonomic and flexible work environment around the meeting table.

- Many different size options
- Ergonomic
- Design it yourself

AERO frame for meeting tables in a robust design, with electric height-adjustment, allows the creation of an ergonomic and flexible work environment at tables where many people meet. Because AERO can be assembled together with any table top and is available in a range of sizes, creating a table to suit the needs of the business or activity is easy. Rectangular legs in an elegant design.

Art. no	Feet	Colour	Height
505140 + 502370	_reL_2588	Chrome	1050
505150 + 502370	_reL_2596	Chrome	1050
505148 + 502378	_reL_2588	Silver	1050
505158 + 502378	_reL_2596	Silver	1050
505145 + 502375	_reL_2588	Black	1050
505155 + 502375	_reL_2596	Black	1050
505146 + 502376	_reL_2588	White	1050
505156 + 502376	_reL_2596	White	1050
505140	_reL_2588	Chrome	700
505150	_reL_2596	Chrome	700
505148	_reL_2588	Silver	700
505158	_reL_2596	Silver	700
505145	_reL_2588	Black	700
505155	_reL_2596	Black	700
505146	_reL_2588	White	700
505156	_reL_2596	White	700
505140 + 502360	_reL_2588	Chrome	900
505150 + 502360	_reL_2596	Chrome	900
505148 + 502368	_reL_2588	Silver	900
505158 + 502368	_reL_2596	Silver	900
505145 + 502365	_reL_2588	Black	900
505155 + 502365	_reL_2596	Black	900
505146 + 502366	_reL_2588	White	900
505156 + 502366	_reL_2596	White	900
505950	_reL_2588	Chrome	700-1000
505960	_reL_2596	Chrome	700-1000
505958	_reL_2588	Silver	700-1000
505968	_reL_2596	Silver	700-1000
505955	_reL_2588	Black	700-1000
505965	_reL_2596	Black	700-1000
505956	_reL_2588	White	700-1000
505966	_reL_2596	White	700-1000

Technical specifications

AERO C-4



Specification	Value
Adjustable height	Yes
Powered by	Electricity
Frame width	3360 - 5205 mm
Stroke	400 mm (675 - 1075 mm ± 5 mm)
Lift capacity	Max 100 kg
Speed	30 mm/sek
Standby power	0,3 W
Noise level	< 42 dBa
Dimensions tabletops	3380 - 5905 mm x 800 - 1500 mm
Certifications	SS EN 15372 CE Compliant
Duty cycle	10%, 1 min/9 min pause. Max 2 min/18 min
Installation height down position	675 mm
Paintwork	Powder coating
Area of use	Indoor environment Ambient temperature: +5° to +30° C Humidity: 5 - 85% non condensed
Control unit performance	Low inbuilt height dimensions Switching technology without any magnetic fields Inbuilt overload protection Inbuilt temperature protection
Lifetime	Min 10 000 cycles