## SWEDSTYLE



## CLASSIC 2.0 FLEX-2022 2column

New generation CLASSIC desk frame. Sit & Stand frame with electric motor for a straight desktop. Stable design with continuous height adjustment control for ergonomic working positions.

- Flexible height
- Ergonomic
- Elegant legs of rectangular design

CLASSIC straight electric Sit & Stand frame, with continuous height adjustment control, makes it easy for the user to create an ergonomic work environment. Robust and flexible design that can be adjusted lengthways ensures a reliable desk that is easily adapted to the desktop of your choice. Free-standing legs mean optimum freedom of movement thanks to unrestricted leg room. Elegant legs of rectangular design with the big leg at the bottom. Based on the latest technology in height adjustment control to ensure reliable and comfortable operation.

| Colour     | Stand sections                |
|------------|-------------------------------|
| Anthracite | 3-stage                       |
| Silver     | 3-stage                       |
| Black      | 3-stage                       |
| White      | 3-stage                       |
|            | Anthracite<br>Silver<br>Black |



## **Technical specifications** CLASSIC 2.0 FLEX-2022 2column



| Specification            | Value  |  |
|--------------------------|--|--|
| Adjustable height        | Yes  |  |
| Powered by               | Electricity  |  |
| Frame width              | 1150 - 1740 mm   |  |
| Lift capacity            | Max 100 kg   |  |
| Standby power            | 0,3 W  |  |
| Noise level              | < 42 dBa   |  |
| Dimensions tabletops     | 1160 - 2200 mm x 550 - 800 mm  |  |
| Duty cycle               | 10%, 1 min/9 min pause. Max 2 min/18 min   |  |
| Paintwork                | Powder coating   |  |
| Area of use              | Indoor environment<br>Ambient temperature: +5° to +30° C<br>Humidity: 5 - 85% non condensed  |  |
| Control unit performance | Low inbuilt height dimensions<br>Switching technology without any magnetic fields<br>Inbuilt overload protection<br>Inbuilt temperature protection |  |
| Lifetime                 | Min 10 000 cycles  |  |

